

KAL790

Kilsen Addressable Fire Door Controller - IO Unit

General

The KAL700 series modules include a complete range of interfaces developed for I/O control on addressable fire systems running Kilsen protocol, housed in easy to install, IP55 housings. These modules allow the fire system to perform additional building management functions during fire situations. 125 I/O addresses are available on every fire panel loop in addition to 125 fire detector addresses.

KAL700 Fire Door Controllers

The KAL790 provides a remote input for monitoring of the fire door, together with a potential free relay output for door magnet control, directly on the fire system loop. The input is constantly monitored for status change whilst the output provides a fail-to-safe control for the fire door. A facility to monitor the auxiliary supply controlling the door magnet is included.

Installation

The KAL700 Series is designed for surface mount installation. Addressing on the modules is done via easy to use DIP switches. The KAL790 may be configured for external or loop power.

Applications

The KAL790 is intended for use on firebreak doors with hold-open door magnets. In case of an alarm, the fire panel instructs the unit to release the door magnet, whilst the input monitor ensures that the door is properly closed. In case of a power failure to the door magnet, the auxiliary supply monitor notifies the panel and an alarm is raised.

Having the control relay in fail-to-safe mode allows the relay to drop out in case of power failure to the unit, allowing the fire door to close normally and ensuring the integrity of fire area.



Details

- EN54:18 and CPD certified
- Surface mount
- Easy addressing
- External or loop powered
- Local alarm and communications indication
- Fire door control and status monitoring
- Part of a family of I/O modules consisting of: -Conventional zone monitors -Digital input modules -Extinguishing control modules -Loop Isolators -Manual call points -Relay and supervised output units -Fire door controllers

KAL790

Kilsen Addressable Fire Door Controller - IO Unit

Technical specifications

General

Status indication	LEDs
Compatibility	Kilsen KL7A systems

Electrical

Power supply type	24 VDC
Operating voltage	22 to 38 VDC
Current consumption	External supply: 110 µA @ 24 VDC from the loop (Quiescent) 135 µA @ 35 VDC from the loop (Quiescent) 10 mA from the loop (Active) 200 µA external (Quiescent) < 50 mA external (Active) Loop power: 350 µA (Quiescent) < 3.4 mA (Active)

Input

Input quantity	1
Input type and rating	Unsupervised
Termination resistor	NA

Output

Output quantity	1
Output type and rating	Potential free, 0.5A @ 42 VAC/ 0.5 A @ 30 VDC
Termination resistor	NA

Physical

Physical dimensions	150 x 110 x 70 mm
Net weight	370 g
Colour	Grey
Mounting type	19" rack, Surface mount
Cable entries	10

Environmental

Vandal proof	No
Operating temperature	-10 to +50°C
Storage temperature	-10 to +70°C
Relative humidity	0 to 95% noncondensing
Environment	Indoor
IP rating	IP55

Regulatory

Compliance	CE, REACH, RoHS 2, WEEE
Certification	CPR
Standards	EN54-18



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 7 April 2023 - 13:40