

# KAL755

## KL7A Series Compatible Intelligent Addressable Manual Call Point - Red

### General

---

The KAL750 Series is an intelligent KL7A range of addressable manual call points. The KAL755 is a red, single action indoor MCP. It is delivered complete with resettable element, test connector and test key. Multiple optional accessories are available to facilitate most indoor installation requirements.

### Aesthetics

---

This single action MCP is a standard profile, indoor MCP suitable for surface and flush mount installations using standard or legacy European electrical boxes. With its designer dual, tricolour LEDs it offers 180°, clear local indication of its operational status, even from a side view in a passage installation. The clean face of the MCP is further enhanced by a front access & test key facility that allows access to the back box and cabling, making additional fastening screw holes obsolete.

### Configuration Friendly

---

Electronic configuration and addressing is possible wirelessly (powered or unpowered).

### Installation & Maintenance Friendly

---

The front facing access for an aesthetically matching, red MCP test key allows unhindered access regardless of the installation location. The MCP key doubles as a test and disassembly tool allowing removal of the MCP front cover and access to the back box and cables without the need for additional tools.

### Compatibility

---

The KAL750 series supports new and legacy Kilsen KL7A systems. They can be deployed seamlessly into existing legacy systems without CIE configuration changes.



### Details

---

- Reliable single action manual call point for surface and flush mounting
- Dual, tri-colour status indicators offers 180° alarm visibility
- Tamper resistant design with resettable or frangible element
- Unobtrusive front facing test facility
- Standard mounting options facilitates easy retrofitting to existing installations
- Back box with rear, top and bottom cable entry
- Screen connection terminal for electrically noisy installations
- Pluggable connector with link through facility for ease of installation and pre-commissioning testing
- An alarm flag on the face of the manual call point allows alarm indication even without alarm LEDs
- Fast, no-tools-required maintenance using the test key
- Local system intelligence for full configuration flexibility
- Electronic addressing for 125 addresses
- Unpowered wireless setup, configuration and reporting
- Wireless commission and diagnostics reporting
- Local event, manufacturing and service logs

# KAL755

## KL7A Series Compatible Intelligent Addressable Manual Call Point - Red

### Technical specifications

#### General

Status indication	Dual LEDs Alarm (Red Constant) Isolated (Yellow Constant) Fault (Yellow Blinking) Communication (Green Blinking)
User interface	LEDs, Alarm flag
Compatibility	Kilsen KL7A systems
Event log	32 Events
Connectivity	Loop protocol & RFID
Addressing method	Electronic

#### Electrical

Power supply type	Loop powered
Operating voltage	16 to 42 VDC
Current consumption	240 $\mu$ A (Quiescent) 2.9 mA (Alarm)
Cable specification	0.404 to 2.05 mm
No. of cable cores	2
Terminals	4 (A+/A-;B+/B-)

#### Detection

Detection principle	Push button/switch
Monitoring	Device type, Presence

#### Physical

Physical dimensions	87 × 87 × 26 mm (w/o back box) 87 × 87 × 57 mm (w/ back box)
Net weight	110 g (w/o back box) 170 g (w/ back box)
Colour	Red (RAL 3028)
Mounting type	Back box, Recessed mount, Wall mount
Cable entries	4
Material (body)	Flame retardant ABS
Functional marking	House on Fire
Back box cable knockouts	1 × Ø 20 mm (Back) 1 × Ø 25 mm (Top or bottom) 2 × Ø 20 mm (Bottom or top)

#### Environmental


Vandal proof	No
Operating temperature	-25 to +72°C
Storage temperature	-25 to +72°C
Relative humidity	10 to 95% noncondensing
Environment	Indoor
IP rating	IP41

#### Regulatory

Compliance	CE, REACH, RoHS 2, WEEE
Certification	EN54-11
Standards	CPR Certified

#### Standards & Regulation

Voluntary marks	A+
-----------------	----



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit [firesecurityproducts.com](https://firesecurityproducts.com) online or contact your sales representative.

Last updated on 19 December 2022 - 16:26